



Εξελίσσουμε τις ανάγκες σας

CRS317-1G-16S+RM

MIKROTIK



CRS317-1G-16S+RM

Περιγραφή

Browser GUI

The CRS317-1G-16S+RM is equipped with the "Dual boot" option, which allows you to select the operating system you want to use - RouterOS or SwOS. If you prefer to use the device as a switch, use SwOS. If you are used to Winbox and want to use routing and other third layer protocols, run your device with RouterOS. The device is equipped with an additional processor that allows you to run a complete RouterOS system. Its performance allows you to use some of the features which are not in the switches The device gives you all the basic functions of a managed swich, it also allows port forwarding, MAC address filtering, VLAN configuration, mirror traffic, bandwidth limiting, The CRS317-1G-16S + comes with 16 SFP sockets. It supports both SFP 1.25Gb and 10Gb SFP + modules.

Main features:
1U rack housing
Ability to switching packets in layer two
16k host array
IEEE 802.1Q VLAN
Supports up to 4000 simultaneous VLANs
Isolation of ports
Port security
Control of the Broadcast Storm
Port mirroring for incoming / outgoing traffic
Rapid Spanning Tree Protocol (RSTP)
Access Control List
MikroTik Neighbor Detection Tool
SNMP v1

Κατηγορία

ΔΙΚΤΥΑΚΑ ΠΡΟΪΟΝΤΑ || ΠΑΘΗΤΙΚΟΣ ΕΞΟΠΛΙΣΜΟΣ || ROUTER || ΜΙΚRΟΤΙΚ



