

DE 06-12 Power adaptor 12V / 0.5A

Power adaptor with a 1.1 m flexible cable terminated by a plug is intended for powering Jablotron devices like wireless keyboards, GSM communicators or UC receivers etc. The compact dimensions of the case allow installation into a standard electro-installation junction box for hidden installation beneath Jablotron wall-box-mounted products such as the above-mentioned items. The screw holes for M3 screws are also useful for installation in typical junction boxes where fixing is required.



Installation shall always be provided by a qualified electrician.

Technical specifications

Supply voltage	100 ~ 240 V AC, class protection II
Output voltage	12V DC ($\pm 2\%$)
Output current	500 mA
Peak output current T<5 min	1000 mA
Output power	12 W max.
Short-circuit protection and overload protection	yes
Enclosure protection	IP64
Dimensions	50 x 48 x 25 mm
Input cable	length 110 mm (230 V), diameter 1.3 mm (AWG 16)
Operational conditions according to	EN 50131-1 II. Environmental class
Working temperature range	-10°C to +40°C
Complies with	EN 50130-4, EN 55022, EN 60950-1



JABLOTRON ALARMS a.s. hereby declares that the DE 06-12 is in compliance with the essential requirements and other relevant provisions of Directives 2006/95/EC and 2004/108/EC. The original of the conformity assessment can be found at www.jablotron.com, Technical Support section



Note: Although this product does not contain any harmful materials we suggest you return the product to the dealer or directly to the producer after use.

JABLOTRON
CREATING ALARMS

JABLOTRON ALARMS a.s.
Pod Skalkou 4567/33
46601 Jablonec nad Nisou
Czech Republic
Tel.: +420 483 559 911
Fax: +420 483 559 993
Internet: www.jablotron.com