

Εξελίσσουμε τις ανάγκες σας

UNIFI UAP-OUTDOOR+ UBIQUITY



UNIFI UAP-OUTDOOR+

Περιγραφή

Designed for noisy, high-density environments, the UAP-Outdoor AP+ utilizes our innovative Multi-Lane RF technology to provide superior capacity and throughput. The UAP-Outdoor AP+ includes two external antennas and a secondary Ethernet port for bridging. It supports 802.11n MIMO, with speeds of up to 300 Mbps and a range of up to 183 m (600 ft). It includes two 5dBi external antennas and 2x10/100Mbps Ethernet ports. UAP-Outdoor AP+ supports both 48V passive PoE and 802.3af powering options. Main features Utilize Multi-Lane RF Technology for high-density applications Up to 28dBm 2.4GHz 2x2 MIMO Networking//Wireless interface 2x 10/100Mbps Ethernet ports 48V passive PoE and 802.3af support UniFi Software main features Zero Handoff Roaming Auto-detection of new APs Multi-Site Management Detailed Analytics WLAN Groups Networking//Wireless Uplink Guest Portal/Hotspot Support Multi-Lane RF Technology Networking//Wireless client devices in high-density areas experience significant interference and noise stemming from multiple APs using the same operating band. With the launch of the UniFi AP-Outdoor AP+, Ubiquiti Networks introduces our patented Multi-Lane RF? technology, which optimizes the operating channel and rejects interference using specialized circuitry, the High-Selectivity Receiver (HSR). Our innovative Multi-Lane RF technology isolates signal on the operating channel and removes adjacent channel interference. Networking//Wireless capacity and throughput are increased in high-density areas, and multiple APs can operate in close proximity. When the UniFi AP-Outdoor AP+ operates on channel 6, its HSR filter specifically eliminates all non-channel 6 frequencies, creating a clean spectrum with minimal noise. So with Multi-Lane RF technology, you truly have three high-speed, multi-lane channels (1, 6, and 11) available for superior capacity and throughput.

Τεχνικά Χαρακτηριστικά προϊόντος*

Dimensions	205 x 83 x 37 mm
Weight	250 g (without Antennas) 294 g (with Antennas)
Networking Interface	10/100 Ethernet Ports
Buttons	Reset
Antennas	External 5 dBi Omni Antennas Included 191 mm (Length), 13 mm (Diameter)
Wi-Fi Standards	802.11 b/g/n
Power Method	Passive Power over Ethernet (48V), 802.3af Supported
Power Supply	48V, 0.5A PoE Adapter (Included)
Maximum Power Consumption	8 W
Maximum TX Power	28 dBm
BSSID	Up to Four Per Radio
Power Save	Supported
Networking//Wireless Security	WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i
Certifications	CE, FCC, IC
Mounting	Wall/Ceiling (Kits Included)
Operating Temperature	-30 to 65° C
Operating Humidity	5 - 95% Non-Condensing
VLAN	802.1Q



Για περισσότερες πληροφορίες επισκεφτείτε την ιστοσελίδα του προϊόντος:

http://www.isnet.gr/pegasus/products01/show00.php?code=703&pcode=SHOW_PROD703

Advanced QoS	Per-User Rate Limiting
Guest Traffic Isolation	Supported
WMM	Voice, Video, Best Effort, and Background
Concurrent Clients	100+
Supported Data Rates (Mbps) 802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
Supported Data Rates (Mbps) 802.11b	1, 2, 5.5, 11 Mbps
Supported Data Rates (Mbps) 802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps

*Τα τεχνικά χαρακτηριστικά του προϊόντος μπορεί να αλλάξουν χωρίς προειδοποίηση

Κατηγορία

ΔΙΚΤΥΑΚΑ ΠΡΟΪΟΝΤΑ || ΕΝΕΡΓΟΣ ΕΞΟΠΛΙΣΜΟΣ || ACCESS POINT

Προϊόντα που σχετίζονται με το UNIFI UAP-OUTDOOR+



UNIFI UAP
Ασύρματος δικτυακός
αναμεταδότης



UNIFI UAP-LR
Ασύρματος δικτυακός
αναμεταδότης



UNIFI UAP-PRO
Ασύρματος δικτυακός
αναμεταδότης



UNIFI UAP-AC OUTDOOR
Ασύρματος δικτυακός
αναμεταδότης

Για περισσότερες πληροφορίες επισκεφτείτε την ιστοσελίδα του προϊόντος:

http://www.isnet.gr/pegasus/products01/show00.php?code=703&pcode=SHOW_PROD703



www.isnet.gr || info@isnet.gr || 210 48 30 600